Water Cooled Chiller LX1750WCC

Email: info@labdex.com **website:** www.labdex.com

Description

Water Cooled Chiller LX1750WCC an easy to operate, safe, energy-conscious and low noise equipment designed for continuous operation. They are well equipped with shell and tube condenser along with water pump and digital display. Using highly precise temperature control and high efficiency compressor, they provide stable and efficient performance.

Specifications

Tank capacity	30 L
Temperature range	5°C - 25°C
Total power	3.28 kW
Cooling capacity	7.5 kW 6459 Kcal/h
Evaporator	Tank + Copper coils
Condenser	Shell and tube
Compressor	Hermetic Scroll Type or Piston 2.2 kW
Pump	0.75 kW
Power supply	3 Phase / 380 V / 50 Hz
Dimension	950 x 530 x 950 mm
Weight	95 Kg

Features

- Temperature range: 5°C to 25°C
- Strong cooling ability and button operated screen control
- Overloaded protection from current and pressure protection
- Digital display showing water temperature
- Refrigerant R407C
- Compressor type: Hermetic scroll type/piston
- Stainless steel tank and water pump
- Tank-type evaporator with G1'' inlet and outlet ports

Applications

- Water chiller are used in basically laboratory, cooling processes in plastic industry, electroplating industry, food industry, biotechnology, packaging, laser etc.

71-75 Shelton Street Covent Garden, London WC2H 9JQ UK.

Email: info@labdex.com | Website: www.labdex.com